#### Amendments to the Claims:

This listing of the claims will replace all prior versions, and listings, of claims in the application.

#### Listing of Claims:

(Currently amended) A method for caching secure content in a Secure Reverse 24. Proxy ("SRP") in a secure network, comprising:

coupling at least one SRP among at least one web browser and at least one web server wherein the at least one SRP receives from the at least one web browser requests for establishing a first secure session;

establishing the first secure session using a first secure session protocol between the at least one SRP and the at least one web browser, wherein the at least one web browser sends an encrypted request for content to the at least one SRP;

decrypting the encrypted request for content from the at least one web browser at the at least one SRP using the first secure session protocol, wherein the at least one SRP determines that the at least one SRP does not possess the requested content;

establishing a second secure session using a second secure session protocol between the at least one SRP and the at least one web server, wherein the second secure session is maintained:

encrypting the request for content from the at least one web browser using the second secure session protocol;

sending the encrypted request for content to the at least one web server using the second secure session:

receiving the requested content from the at least one web server at the at least one SRP using the second secure session:

36334 6646 19564		
36321-8010.US01	171	00/001 250
100021 0010,0001	121	09/901,350

decrypting the requested content using the second secure session protocol;

encrypting said the requested content using the first secure session protocol for sending, using the first secure session, to the at least one web browser from the at least one SRP in response to the encrypted request for content from the at least one web browser;

determining if the requested content is a static content;

encrypting the requested content, if the requested content is the static content, using a third secure session protocol for storing the encrypted requested content locally in a memory at the at least one SRP, wherein the third secure session protocol is known only to the at least one SRP;

decrypting the encrypted static content from the memory at the at least one SRP upon subsequent requests for the static content; and

sending the static content to the at least one web browser.

Claim 25 (Canceled)

- 26. (Original) The method of claim 24, wherein storing includes using non-volatile media.
- 27. (Original) The method of claim 24, wherein coupling includes establishing a dedicated secure line between the SRP and the web server.
- 28. (Original) The method of claim 24, wherein coupling includes collocating the web server and the SRP.
- 29. (Original) The method of claim 24, wherein content includes an HTTP page.

26221_0010   ICO1	l a l	00/004 050
36321-8010.US01	131	09/901,350

- 30. (Original) The method of claim 24, wherein the first secure session includes Transport Layer Security protocol.
- 31. (Original) The method of claim 24, wherein the second secure session includes Transport Layer Security protocol.
- 32. (Original) The method of claim 24, wherein the first secure session includes Secure Socket Layer protocol.
- 33. (Original) The method of claim 24, wherein the second secure session includes Secure Socket Layer protocol.
- 34. (Original) The method of claim 24, wherein the first secure session includes Internet Protocol Secure ("IPSec") techniques.
- 35. (Original) The method of claim 24, wherein the second secure session includes Internet Protocol Secure ("IPSec") techniques.
- 36. (Previously presented) The method of claim 29, further comprising, before storing the HTTP page, encrypting the HTTP page.

Claims 37-59 (Canceled)

60. (Original) The method of claim 24, wherein the static content is a banner or a navigation button.

36321-8010	.US01	4	09/901,350

61. (Currently Amended) A method for caching secure content over a network comprising:

establishing a first secure session between a client and a proxy server using a first secure session protocol;

encrypting a request for content at the client using the first secure session protocol:

sending the encrypted request for content from the client to the proxy server using the first secure session;

receiving the encrypted request for content at the proxy server using the first secure session;

decrypting the encrypted request for content at the proxy server using the first secure session protocol;

determining that the content is not available at the proxy server:

establishing a second secure session between the proxy server and a web server using a second secure session protocol;

encrypting the request for content using the second secure session protocol at the proxy server;

sending the encrypted request for content from the proxy server to the web server using the second secure session;

receiving the encrypted request for content at the web server using the second secure session;

decrypting the encrypted request for content at the web server using the second secure session protocol;

encrypting the content at the web server using the second secure session protocol;

36321-8010.US01	5	09/901,350

sending the encrypted content from the web server to the proxy server using the second secure session:

receiving the encrypted content at the proxy server using the second secure session;

decrypting the encrypted content at the proxy server using the second secure session protocol;

determining if the content is a static content at the proxy server;

encrypting the content, if the content is the static content, using a third secure session protocol at the proxy server for storing the static content locally in a memory at the proxy server, wherein the third secure session protocol is known only to proxy server;

encrypting the content at the proxy server using the first secure session protocol; sending the encrypted content from the proxy server to the client using the first secure session:

receiving the encrypted content at the client using the first secure session;

decrypting the encrypted content at the client using the first secure session protocol; and

decrypting the encrypted static content at the proxy server using the third secure session protocol when an additional request for the static content is sent from the client to the proxy server.

(Original) The method of claim 61, wherein a plurality of clients are each securely 62. connected to the proxy server via a plurality of differing secure session protocols and the proxy server is securely connected to the web server via the second secure session protocol in order to retrieve secure content requested by the plurality of clients that is not contained at the proxy server.

36321-8010.US01	6	09/901,350	ĺ

- (Original) The method of claim 61, wherein the static content is a banner or a 63. navigation button.
- (Previously Presented) A method for caching secure content over a network 64. comprising:

establishing a first secure session between a client and a proxy server using a first secure session protocol;

sending an encrypted request for content from the client to the proxy server using the first secure session;

receiving the encrypted request for content at the proxy server using the first secure session:

decrypting the encrypted request for content at the proxy server using the first secure session protocol;

determining that a first part of the content is available at the proxy server and a second part is not available at the proxy server,

establishing a second secure session between the proxy server and a web server using a second secure session protocol to retrieve the second part of the content:

encrypting a second request for the second part of the content using the second secure session protocol at the proxy server;

sending the encrypted second request for the second part of the content from the proxy server to the web server using the second secure session;

receiving the encrypted second request for the second part of the content at the web server using the second secure session;

decrypting the encrypted second request for the second part of the content at the web server using the second secure session protocol;

36321-8010.US01 7 09/901,350

encrypting the second part of the content at the web server using the second secure session protocol;

sending the encrypted second part of the content from the web server to the proxy server using the second secure session;

receiving the encrypted second part of the content at the proxy server using the second secure session:

decrypting the encrypted second part of the content at the proxy server using the second secure session protocol;

determining if the second part of the content is a static content at the proxy server;

encrypting the second part of the content, if the second part of the content is the static content, using a third secure session protocol at the proxy server for storing the static content locally in a memory at the proxy server, wherein the third secure session protocol is known only to proxy server,

decrypting the first part of the content at the proxy server using the third session protocol:

encrypting the first and second parts of the content at the proxy server using the first secure session protocol;

sending the encrypted first and second parts of the content from the proxy server to the client using the first secure session;

receiving the encrypted first and second parts of the content at the client using the first secure session;

decrypting the encrypted second and first parts of the content at the client using the first secure session protocol; and

decrypting the first and second parts of the content at the proxy server using the third secure session protocol when an additional request for the first and the seconds parts of the content is sent from the client to the proxy server.

- 1	[ <del> </del>				
	36321-8010.US01				
	45 4 / 1 28 ()			09/901	750 1
	.,\.,\Z_1_OD_1O_(\)	1 13		41070311	2611
		, -	I U	U212UL	
- 4		 	J		/~~~ I

- (Original) The method of claim 64, wherein a plurality of clients are each securely 65. connected to the proxy server via a plurality of differing secure session protocols and the proxy server is securely connected to the web server via the second secure session protocol in order to retrieve secure content requested by the plurality of clients that is not contained at the proxy server.
- (Original) The method of claim 64, wherein the static content is a banner or a 66. navigation button.

#### 67. (Original) A method comprising:

establishing a first secure session between a client and a secure reverse proxy (SRP), wherein the first secure session prevents intermediate storing of secure static content on a reverse proxy;

receiving a request for content from the client at the SRP, wherein the requested content is uncached at the SRP:

establishing a second secure session between the SRP and a web server, wherein the second secure session prevents intermediate storing of secure static content on a reverse proxy;

in response to the request for content:

obtaining, by way of the second secure session, secure static content from the web server at the SRP;

caching the secure static content at the SRP:

sending, by way of the first secure session, the secure static content from the SRP to the client.

26224 0040 HCO4	1.5	
36321-8010.US01	10	09/901,350
30321 0010.0301	1 2	1 49/907330 1
A STATE OF THE STA		,,

- (Currently Amended) The method of claim 67, wherein said caching the secure static content results in a reduced number of requests at the web server for encrypted content.
- (Original) The method of claim 67, wherein the first secure session is a TLS 69. session.
- (Original) The method of claim 67, wherein the second secure session is a TLS 70. session.

	<del></del>	
36321-8010.US01	10	00 (001 050
20251-00T0'020T	[ 10 ]	09/901,350